Soft Button Display

The SBD design integrates smart intercom, ZigBee gateway and home automation.



ii

Dus harre





Product Overview

The "Soft Button Display" is a smart home center panel with a Linux operating system. The ALL IN ONE design integrates smart intercom, ZigBee gateway and home automation, and is compatible with plentiful ecosystem. Multimodal interaction can be easily used by the whole family, offering the excellent smart home experience.



3.27" touch screen with energy saving mode

2-gang switch, replace conventional switch

4 metal buttons, suitable for the whole family





Smart intercom, ZigBee gateway, home automation ALL IN ONE



Kinds of sensors built-in

EU standard flush mounted box



Product Specification 8000008 0000 **(5) BOTTOM VIEW** 47.4 08 35.6 11.8 86.0 . 30 Mar. 3 50.0 86.0 Tuesday 0000 26 c / 40 (2) **RIGHT VIEW** (4) **BACK VIEW** (1) FRONT VIEW (3) LEFT VIEW 50.0

 \bigcirc TOP VIEW

A 50mm deep electrical box is highly recommended for ease of installation. In some scenarios, especially when the wires can be pushed back into the wall far enough, it may be possible to use a 40mm deep box.





Technical Information

Technical Specifications

- Model Number: SBD-R2-EU
- Power Supply: 220Vac±20%
- **Operation System: Linux**
- DDR/Flash: 128MB/ 256MB
- Wi-Fi: IEEE802.11 b/g/n, @2.4GHz
- Bluetooth: BLE 4.2

Connectivity and Features

- Ethernet ports: 1xRJ45, 10/100Mbps adaptive
- ZigBee: ZigBee 3.0 •
- Relays out: 2-gang
- Microphone: Dual microphone,-26DBFS
- Speaker: Single speakers, 8Ω / 1.5W •



Built-in Sensors

\mathcal{O}

Proximity Sensor

Detects nearby objects or user presence

Range: 30~60cm



Light Sensor

Measures ambient light levels

Low-level lux detection



Temperature Sensor

Monitors room temperature	M
	le
Λ_{00} μ_{00} μ_{10}	Δ

Accuracy: ±1°C, Range: -10°C~55°C Accuracy: ±5%, Range: 10%~90%RH,

without condensation





Humidity Sensor

leasures air moisture evels

Working Environment and Installation

Working Environment

- Environment: For indoor use only
- Working Humidity: 10~90%
- Working Temperature: $-10^{\circ}C \sim +55^{\circ}C$
- Storage Temperature: -20°C ~ +65°C ۲

Installation Details

- Installation: Wall flush mounting
- Flush Mounted Module: EU/GB standard
- Wiring Way: Line & Neutral

